

Fast-Set Plural-Component Equipment

For Foam and Coatings Applications



PROVEN QUALITY. LEADING TECHNOLOGY.

Engineered for Performance

Expect superior foam and coatings results with Graco® Plural-Component Equipment



Complete systems for superior results

Whether you're spraying polyurethane foam or applying polyurea, Graco Reactor® Plural-Component Systems help you get the job done with superior results.

From entry-level models to high-output systems, there is a Graco Reactor that's ideal for your application.

Applications:

Polyurethane Foam

- Residential wall insulation
- Rim and band joist
- Roof insulation
- Aerospace
- Commercial walls
- Concrete lifting

Coatings

- Concrete joint filling
- Marine and shipbuilding
- Potable water
- Wastewater treatment
- Truck bedliners
- Secondary containment
- Adhesives and caulk
- Waterproofing
- Tank and pipe coating
- Foundations

Build a complete system in just a few steps

1 SELECT A SYSTEM

Choose an air, electric or hydraulic model.

KEY FEATURES:

- Optional data reporting capabilities
- Foam models rated at 2000 psi (138 bar, 13.8 MPa)
- Coatings models rated up to 3500 psi (240 bar, 24.0 MPa)

2 SELECT HEATED HOSES

Choose from pressure ratings of 2000 psi or 3500 psi (138 to 240 bar, 13.8 to 24.0 MPa).
Choose 3/8 in or 1/2 in IDS.

3 SELECT HEATED WHIP HOSE

Choose from pressure ratings of 2000 psi or 3500 psi (138 to 240 bar, 13.8 to 24.0 MPa).
Choose 1/4 in or 3/8 in IDS.

4 SELECT A GUN

Choose an air-purge, mechanical-purge or liquid-purge gun with a round or flat pattern.

5 SELECT SUPPLY PROCESSING EQUIPMENT


5 SUPPLY PUMP

Choose from diaphragm or piston pumps for standard materials in drum-mount or wall-mount. Select a 2:1 piston pump for materials with higher viscosities.

6 AGITATOR KITS

Choose a kit to agitate your resin for a consistent coating. Graco's patented Twistork® agitators are very low shear to minimize material frothing.

For details on hoses, guns and accessories, see brochure 349104.



Air, Electric and Hydraulic Systems

No matter what the application, Graco has the solution



Which system is right for you?

AIR-DRIVEN

- Entry-level system
- Low-output applications
- Easy to use
- Minimal system feedback for operator



Reactor® A-25

ELECTRIC

- The most popular system
- High value for great performance
- Mid- to high-output applications
- Provides operator with material data and system diagnostics for total control



Reactors E-8p, E-10, E-10hp, E-20, E-30, E-XP1, E-XP2, E-30i, E-XP2i

HYDRAULIC

- Top of the line system for high-production professionals
- Highest value for the greatest performance
- High-output applications
- Ideal for in-plant OEMs
- Provides superior, uninterrupted performance
- Provides operator with material data and system diagnostics for total control



Reactors H-25, H-40, H-50, H-XP2, H-XP3

PERFORMANCE CHARTS

Use these charts to help identify the system that will work most efficiently with each mix chamber. Flow rates are based on a material viscosity of 60 cps. See examples below.

HOW TO USE THESE GRAPHS

- Select spray pressure
- Select mix chamber or flow rate
- Choose proportioner model

Note: Darker shading includes proportioner models shown in lighter shaded areas.

FOAM EXAMPLE


Mix chamber: AR6060 (03)
Pressure: 1250 psi
Flow rate: 22 lb/min*
Reactors H-25, E-30, H-40, H-50

COATING EXAMPLE


Mix chamber: AR2929 (00)
Pressure: 1500 psi
Flow rate: 0.9 gpm*
Reactors E-XP1, E-XP2, H-XP2, H-XP3, E-10hp (230V)

* Output of flat tip will be slightly less than round equivalent.

SPRAY FOAM EQUIPMENT



COATINGS EQUIPMENT



Air-Driven Equipment

Easy-to-use, entry-level system for low-output applications

Reactor A-25: Superior performance with long-lasting durability

The Reactor A-25 is a Graco-engineered spray foam proportioner that gives you the reliability you expect on the jobsite. It maintains consistent temperature control, even when you're spraying at maximum flow rates - resulting in better quality foam.

- Maintains temperature setpoints for better yield
- Maintains consistent output pressure for uniform spray pattern
- Easy to operate and maintain
- Best choice for affordability and long-lasting durability



DataTrak™ Control

- Resettable counter tracks material usage

Three Heat Zones

- Three independent heat zones – ISO, resin and hose heat
 - Provide accurate heat control for reliable spraying to handle different chemical viscosities
 - Digital temperature controls

Recirculation Manifold

- A quick, easy way to balance system pressures

NXT® Air Motor

- Low air consumption for increased efficiency
- Muffler provides low operating noise levels
- Air valve provides smooth and rapid changeover

Hybrid Heater

- Provides better temperature control

Quick Knockdown Lower Pumps

- For easy disassembly and maintenance

ISO Pump Lube System

- Prevents isocyanate crystallization on the pump seal and shaft



Electric Equipment

Preferred choice for medium- to high-output foam or coatings applications

Reactor E-Series: High performance at an outstanding value

Equipped with material data and system diagnostics, Reactor E-Series proportioners provide total control. Advanced features provide longer equipment life, more uptime for your spray day and overall Graco reliability. From entry-level models to high-output systems, there's a Reactor system that's ideal for your specific application.

- Easy to use, easy to learn – reduces training time and increases productivity
- Circulation valves with longer lasting seals
- Longer lasting modular heater control boards that minimize downtime
- Heat transformers that don't require tap settings
- Models include E-8p, E-10, E-10hp, E-20 and E-XP1

Discover the benefits of Reactor²

- Advanced control technology tracks, monitors and saves project data
- Graco InSite™ Remote Reporting Technology (with Elite models)
- Troubleshooting made easy with on-screen QR code shortcuts
- Compact design saves room in your spray rig
- Reactor 2 models include E-30, E-XP2 and E-30i, E-XP2i



For Reactor 2 details, see brochure 348986.



PROVEN RELIABILITY

◀ Reactor E-20 and E-XP1

With proven reliability in the field, the Reactor E-20 and E-XP1 systems are designed to apply foam, polyurea and other materials that require accurate temperatures and pressures necessary for superior coating results.

- Easy to use
- Accurate heating with precise temperature sensing
- Portable, wheeled cart lets you get closer to the job

Portable Electric Equipment

Portable entry-level systems

Reactor E-10hp: Expand your business with polyurea applications

The Reactor E-10hp™ is great for coating projects such as terraces, balconies, pools, tanks, containment, waterproofing and bedliner applications. It's a smart, affordable investment that will help your business grow. And even though it's an entry-level system, it still packs plenty of power. The Reactor E-10hp adds high pressure to give you the power and performance you need to spray polyurea coatings.

- Heats material fast – quick startup times
- Portable, lightweight and easy to use
- Uses standard residential electrical outlets – no generator needed
- Affordable investment – compared to a standard Reactor which requires a generator and spray rig

Low Level Sensors

- Indicates when material is low (1 gal / 3.8 L remaining)
- No contact with materials – prevents buildup

Boost Heat

- Directs unused power from the motor circuit to additional heater rods
- Additional heater power brings material to desired temperatures faster during recirculation mode

Digital Heat Controls

- Allows you to enter the exact temperatures you need
- Uses the same circuit boards as a standard Reactor

Single Knob Motor Operation

- Intuitive, easy to use

Robust Hybrid Heater

- More power, faster material heating means more uptime

Motor

- Offers 50% more power than the Reactor E-10
- Provides improved spray performance with reduced pressure drop

Quick Knockdown Lower Pumps

- Easy disassembly and maintenance

Temperature Gauges in Y-strainers

- Provides accurate tank temperature readings

Insulated Tanks

- Double-wall insulated to retain heat
- Smooth interior lining for easy cleaning
- Improved seal design on lid for better moisture control



For more details, see brochure 349015.



COMPACT AND PORTABLE

◀ Reactor E-10

Get smaller jobs done fast without sacrificing performance. Graco's portable E-10 sprayers are ideal for plural-component spray, joint-fill jobs and touch-ups.

- Electric power is low draw and plugs into standard outlets
- Intuitive start, stop and digital temperature display with single knob operation
- Easy-to-service fluid section reduces maintenance and increases productivity
- Electric motor improves performance and reduces operating costs
- Heaters and hose give up to 2000 watts to pre-heat circulating material

Applications

Foam Insulation

- Rim joists
- Roof patching
- Prep work
- Window repair

Coatings

- Small industrial jobs
- Concrete joint filling and flooring applications
- Small tank spraying using cold spray polyurea
- Industrial maintenance
- Hybrid polyureas

Portable Electric Equipment

Grow your business with professional equipment solutions

Reactor E-8p: For no-heat foams and flooring applications

Become more competitive in today's market with equipment designed for remodeling or flooring applications. As a touch-up system for no-heat foam insulation, the Reactor E-8p frees up larger rigs for larger jobs while enabling you to finish the job affordably. For flooring applications, the Reactor E-8p offers easy control and is ideal for small to mid-sized joint fill applications.



Telescoping Handle

- Easy handling from your vehicle to the home

Built-in Suction Lines

- No need for feed pumps

Pressure Balance Valves

- Quick and easy balancing of system pressures enables correct start-up

Electric Motor

- Proven motor performance and reduced operating costs; plugs into a standard residential outlet

For more details see brochure 348959 and 340831.

Threaded Bucket Spout Connection

- Keeps your connection secure and prevents spills

Lightweight and Portable


- Easy to maneuver up and down stairs, wherever the job goes – only 95 lb (43 kg)

Simple User Controls

- Intuitive start/stop with single control knob operation

2K Manual Dispense Gun

- Airless gun for maximum portability
- Static mixer ideal for joint fill materials
- Choose from various restrictor options to fit your unique material needs
- Compatible with Reactor E-8p and unheated Reactor E-10



Hydraulic Equipment

Top of the line equipment for high-production professionals

Reactor H-Series: Superior power and performance

Graco's line of hydraulic Reactors brings increased yield and performance to high-output spraying. Hydraulic systems are the choice of spraying professionals who want to reap the benefits of the latest spraying technologies and add productivity to boost their bottom line.

- Adjustable pressure imbalance for tighter or looser ratio error detection
- Flexibility to change A or B pumps for fixed ratio application other than 1:1
- Models include: H-25, H-40, H-50, H-XP2, H-XP3 and H-VR

Digital Heat and Pressure Controls

- Allow you to precisely program temperatures and pressures, and monitor machine performance

Circulation Valves

- Reduce isocyanate crystallization while offering more controlled pressure balancing

Hose Control

- Reliable and accurate hose connection system. Flexible fluid temperature sensor allows you to monitor and control temperature closer to the gun.

ISO Pump Lube System

- Prevents isocyanate crystallization on the pump seal and shaft

Powerful Hybrid Heaters

- Heat material quickly and maintain temperature set points – even when spraying at maximum flow rates

Horizontal Pumps


- Positive displacement pumps are easy to service and provide smoother changeover for maintaining best spray pattern

Troubleshooting Y-Strainer

- Analog temperature and pressure gauges are standard

Heat Platform

- Circuit board is divided into easy-to-replace modules that simplify troubleshooting and maintenance, maximizing spray time



VARIABLE RATIO DISPENSING

◀ Reactor H-VR – Variable Ratio Hydraulic Proportioner

The Reactor H-VR is a variable ratio proportioner that combines proven Graco hydraulic Reactor technology with variable ratio capabilities.

- For applications that require a range or difference in volumetric ratio
- Infinitely adjustable volume ratio from 1:1 to 2.5:1
- Dispenses polyurethane foams and polyurea coatings
- Rated for 3500 psi max working pressure
- 15,300 watt heaters

Ordering Information

Gun and hose sold separately

256886 Reactor H-VR, 230-volt, 3-ph

256887 Reactor H-VR, 400-volt, 3-ph

Integrated Systems

A true Graco-engineered solution

Reactor² E-30i and E-XP2i: Ready for the jobsite or spray rig - right out of the box

A complete system for polyurethane foam or polyurea applications, the integrated series of Reactor proportioning systems combines an electric Reactor and a diesel generator into one package. Complete turnkey models are also available with an integrated air compressor

- Saves diesel fuel costs – on average of \$7,000 annually*
- Improves productivity – with advanced, easy to use controls
- Eliminates guesswork – the system is totally engineered and tested by Graco
- Eliminates costly power issues associated with shore power and low cost generators
- Start spraying sooner – with improved heating capacity
- Improves spray performance – with consistent pressure at the gun
- Saves time – easy to install into a spray rig since it's prewired with components already selected and installed
- Reduces fuel costs even more – compact, portable design fits into a smaller trailer and a smaller trailer means a smaller truck

* By replacing a standard 40 kw generator with a 20 kw generator, the system's fuel needs are greatly reduced. Savings are an estimate only. Actual savings may vary.

Integrated Air Control Panel

- Controls A and B feed pumps, agitator and gun
- One air line connection means less plumbing, less hoses and less assembly time

Heat Recovery System

- Recovers heat from the engine coolant and transfers it to the A and B materials

Refrigerated Air Dryer

- Self-draining
- No need to replace desiccant

Gen Set Controls

- Integrated controls allow for convenient and easy start up
- Engine monitoring functionality

Advanced Controls


- Stores up to 24 material recipes
- Troubleshooting made easy with QR codes
 - USB downloadable job data
- User settable pressure imbalance and low chemical shutdown
 - Manual hose heat mode

Tankless Air Compressor

- No tank saves space
- No need to drain tank

Motor Control

- Consistent pressure at the gun for improved spray performance
- Low-pulse design reduces pump change-over fluctuation



For technical specifications and ordering information see brochure 348986.

Graco Equipment for Foam and Coatings

Technical Specifications and Ordering Information



SPRAY FOAM EQUIPMENT

	Air-Driven	Electric (E Series)				Hydraulic (H Series)
MODEL	A-25	E-8p	E-10	E-20	Reactor 2 E-30	H-25
Max Working Pressure	2000 psi (138 bar, 13.8 MPa) 28 scfm air consumption@100 psi	2000 psi (140 bar, 14 MPa)	2000 psi (138 bar, 13.8 MPa)	2000 psi (138 bar, 13.8 MPa)	2000 psi (138 bar, 13.8 MPa)	2000 psi (138 bar, 13.8 MPa)
Min Working Pressure	N/A	NA	N/A	N/A	N/A	850 psi (59 bar, 5.9 MPa)
Max Hose Length	210 ft (64 m)	105 ft (32 m)	105 ft (32 m)	210 ft (64 m)	310 ft (94 m)	310 ft (94 m)
Max Fluid Temp	190°F (88°C)	NA	160°F (71°C)	190°F (88°C)	190°F (88°C)	190°F (88°C)
Output	25 lb (11.4 kg)/min	.00352 gpm (0.0133 lpm)	12 lb (5.4 kg)/min	20 lb (9 kg)/min	30 lb (13.6 kg)/min	22 lb (10 kg)/min
Weight	250 lb (113 kg)	95 lb (43 kg)	Heated: 160 lb (72 kg) Unheated: 150 lb (68 kg)	342 lb (155 kg)	355 lb (161 kg)	8 kW: 535 lb (243 kg) 15 kW: 562 lb (255 kg)
Ordering Information	<p>With 6.0 kW heater:</p> <p>40A–230V, 1-ph 262614 (Bare) AP2614 (AP Pkg) CS2614 (CS Pkg) P22614 (P2 Pkg)</p> <p>32A–230V, 3-ph 262614 (Bare) AP2614 (AP Pkg) CS2614 (CS Pkg) P22614 (P2 Pkg)</p> <p>18.5A–380V, 3-ph (4-wire) 262614 (Bare) AP2614 (AP Pkg) CS2614 (CS Pkg) P22614 (P2 Pkg)</p>	<p>Foam:</p> <p>120V 259082 (Bare) AP9082 (AP Pkg) CS9082 (CS Pkg) P29082 (P2 Pkg)</p> <p>Flooring:</p> <p>120V 259082 (Bare) 24R151 (Pkg)</p> <p>230V 259083 (Bare) 24R154 (Pkg)</p>	<p>With 1.7 kW heater:</p> <p>120V, 2-cord 249570 (Bare) AP9570 (AP Pkg) CS9570 (CS Pkg)</p> <p>With 2.0 kW heater:</p> <p>240V, 2-cord 249571 (Bare) AP9571 (AP Pkg) CS9571 (CS Pkg)</p> <p>240V, 1-cord 249572 (Bare) AP9572 (AP Pkg) CS9572 (CS Pkg)</p> <p>Unheated ambient system:</p> <p>120V 249576 (Bare) 249806 (Pkg)</p> <p>240V 249577 (Bare) 249808 (Pkg)</p>	<p>With 6.0 kW heater:</p> <p>48A–230V, 1-ph 259025 (Bare) AP9025 (AP Pkg) CS9025 (CS Pkg) P29025 (P2 Pkg)</p> <p>32A–230V, 3-ph 259034 (Bare) AP9034 (AP Pkg) CS9034 (CS Pkg) P29034 (P2 Pkg)</p> <p>24A–400V, 3-ph 259030 (Bare) AP9030 (AP Pkg) CS9030 (CS Pkg) P29030 (P2 Pkg)</p>	<p>Elite</p> <p>With 10.2 kW heater:</p> <p>272110 (Bare) AP2110 (AP Pkg) CS2110 (CS Pkg) P22110 (P2 Pkg)</p> <p>With 15.3 kW heater:</p> <p>272111 (Bare) AP2111 (AP Pkg) CS2111 (CS Pkg) P22111 (P2 Pkg)</p> <p>Standard</p> <p>With 10.2 kW heater:</p> <p>272010 (Bare) AP2010 (AP Pkg) CS2010 (CS Pkg) P22010 (P2 Pkg)</p> <p>With 15.3 kW heater:</p> <p>259057 (Bare) AP9057 (AP Pkg) CS9057 (CS Pkg) P29057 (P2 Pkg)</p> <p>*Amps:</p> <p>10 kW: 230V 1-ph — 78 230V 3-ph — 50 400V 3-ph — 34</p> <p>15 kW: 230V 1-ph — 100 230V 3-ph — 62 400V 3-ph — 35</p>	<p>With 8.0 kW heater:</p> <p>69A–230V, 1-ph 255400 (Bare) AP5400 (AP Pkg) CS5400 (CS Pkg) P25400 (P2 Pkg)</p> <p>46A–230V, 3-ph 255401 (Bare) AP5401 (AP Pkg) CS5401 (CS Pkg) P25401 (P2 Pkg)</p> <p>35A–400V, 3-ph 255402 (Bare) AP5402 (AP Pkg) CS5402 (CS Pkg) P25402 (P2 Pkg)</p> <p>With 15.3 kW heater:</p> <p>100A–230V, 1-ph 255406 (Bare) AP5406 (AP Pkg) CS5406 (CS Pkg) P25406 (P2 Pkg)</p> <p>59A–230V, 3-ph 255407 (Bare) AP5407 (AP Pkg) CS5407 (CS Pkg) P25407 (P2 Pkg)</p> <p>35A–400V, 3-ph 255408 (Bare) AP5408 (AP Pkg) CS5408 (CS Pkg) P25408 (P2 Pkg)</p>
Operation manual	3A1569	3A1602	311075	312065	333023	312062
Repair manual	3A1570	3A1602	311075	312066	333024	312063

Packages include spray hose, whip hose and gun.

*Reactor 2 systems can be wired for all voltages: 230V-1ph; 230V-3ph; 400V-3ph



COATINGS EQUIPMENT

		Electric (E Series)			Hydraulic (H Series)	
H-40	H-50	E-10hp	E-XP1	Reactor 2 E-XP2	H-XP2	H-XP3
2000 psi (138 bar, 13.8 MPa)	1700 psi (117 bar, 11.7 MPa) 1-ph 2000 psi (138 bar, 13.8 MPa) 3-ph	3000 psi (206 bar, 20.6 MPa)	2500 psi (172 bar, 17.2 MPa)	3500 psi (240 bar, 24.0 MPa)	3500 psi (240 bar, 24.0 MPa)	1-ph: 3200 psi (221 bar, 22.1 MPa) 3-ph: 3500 psi (240 bar, 24.0 MPa)
600 psi (41 bar, 4.1 MPa)	600 psi (41 bar, 4.1 MPa)	NA	N/A	N/A	1200 psi (83 bar, 8.3 MPa)	850 psi (59 bar, 5.9 MPa)
410 ft (125 m)	410 ft (125 m)	105 ft (32 m)	210 ft (64 m)	310 ft (94 m)	310 ft (94 m)	410 ft (125 m)
190°F (88°C)	190°F (88°C)	170°F (77°C)	190°F (88°C)	190°F (88°C)	190°F (88°C)	190°F (88°C)
45 lb (20 kg)/min	52 lb (23.6 kg)/min	1 gpm (3.8 lpm)	1.0 gpm (3.8 lpm)	2.0 gpm (7.6 lpm)	1.5 gpm (5.7 lpm)	2.8 gpm (10.6 lpm)
597 lb (271 kg)	597 lb (271 kg)	239 lb (108 kg)	342 lb (155 kg)	350 lb (159 kg)	562 lb (255 kg)	597 lb (271 kg)
<p>With 12.0 kW heater: 100A–230V, 1-ph 253400 (Bare) AP3400 (AP Pkg) P23400 (P2 Pkg)</p> <p>With 15.3 kW heater: 71A–230V, 3-ph 253401 (Bare) AP3401 (AP Pkg) P23401 (P2 Pkg)</p> <p>41A–400V, 3-ph 253402 (Bare) AP3402 (AP Pkg) P23402 (P2 Pkg)</p> <p>With 20.4 kW heater: 95A–230V, 3-ph 253407 (Bare) AP3407 (AP Pkg) P23407 (P2 Pkg)</p> <p>52A–400V, 3-ph 253408 (Bare) AP3408 (AP Pkg) P23408 (P2 Pkg)</p>	<p>With 12.0 kW heater: 100A–230V, 1-ph 253725 (Bare) AP3725 (AP Pkg) P23725 (P2 Pkg)</p> <p>With 15.3 kW heater: 71A–230V, 3-ph 253726 (Bare) AP3726 (AP Pkg) P23726 (P2 Pkg)</p> <p>41A–400V, 3-ph 253727 (Bare) AP3727 (AP Pkg) P23727 (P2 Pkg)</p> <p>With 20.4 kW heater: 95A–230V, 3-ph 256505 (Bare) AP6505 (AP Pkg) P26505 (P2 Pkg)</p> <p>52A–400V, 3-ph 256506 (Bare) AP6506 (AP Pkg) P26506 (P2 Pkg)</p>	<p>120V 24T100 (Bare) APT100 (AP Pkg) P2T100 (P2 Pkg)</p> <p>230V 24T900 (Bare) APT900 (AP Pkg) P2T900 (P2 Pkg)</p>	<p>With 10.2 kW heater: 69A–230V, 1-ph 259024 (Bare) AP9024 (AP Pkg) P29024 (P2 Pkg)</p> <p>43A–230V 3-ph 259033 (Bare) AP9033 (AP Pkg) P29033 (P2 Pkg)</p> <p>24A–400V, 3-ph 259029 (Bare) AP9029 (AP Pkg) P29029 (P2 Pkg)</p>	<p>Elite With 15.3 kW heater: 272112 (Bare) AP2112 (AP Pkg) P22112 (P2 Pkg)</p> <p>Standard With 15.3 kW heater: 272012 (Bare) AP2012 (AP Pkg) P22012 (P2 Pkg)</p> <p>*Amps: 230V 1-ph — 100 230V 3-ph — 62 400V 3-ph — 35</p>	<p>With 15.3 kW heater: 100A–230V, 1-ph 255403 (Bare) AP5403 (AP Pkg) P25403 (P2 Pkg)</p> <p>59A–230V, 3-ph 255404 (Bare) AP5404 (AP Pkg) P25404 (P2 Pkg)</p> <p>35A–400V, 3-ph 255405 (Bare) AP5405 (AP Pkg) P25405 (P2 Pkg)</p>	<p>With 12.0 kW heater: 100A–230V, 1-ph 253403 (Bare) AP3403 (AP Pkg) P23403 (P2 Pkg)</p> <p>With 20.4 kW heater: 95A–230V, 3-ph 253404 (Bare) AP3404 (AP Pkg) P23404 (P2 Pkg)</p> <p>52A–400V, 3-ph 253405 (Bare) AP3405 (AP Pkg) P23405 (P2 Pkg)</p>
312062	312062	332144	312065	333023	312062	312062
312063	312063	332144	312066	333024	312063	312063

Packages include spray hose, whip hose and gun.

*Reactor 2 systems can be wired for all voltages: 230V-1ph; 230V-3ph; 400V-3ph



ABOUT GRACO

PROVEN QUALITY. LEADING TECHNOLOGY.

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS

P.O. Box 1441
Minneapolis, MN 55440-1441
Tel: 612-623-6000
Fax: 612-623-6777

AMERICAS

MINNESOTA

Worldwide Headquarters
Graco Inc.
88-11th Avenue N.E.
Minneapolis, MN 55413

EUROPE

BELGIUM

European Headquarters
Graco N.V.
Industrieterrein-Oude Bunders
Slakweidestraat 31
3630 Maasmechelen,
Belgium
Tel: 32 89 770 700
Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd.
Suite 17, 2 Enterprise Drive
Bundoora, Victoria 3083
Australia
Tel: 61 3 9468 8500
Fax: 61 3 9468 8599

CHINA

Graco Hong Kong Ltd.
Shanghai Representative Office
Building 7
1029 Zhongshan Road South
Huangpu District
Shanghai 200011
The People's Republic of China
Tel: 86 21 649 50088
Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd.
India Liaison Office
Room 443, Augusta Point
Regus Business Centre 53
Golf Course Road
Gurgaon, Haryana
India 122001
Tel: 91 124 435 4208
Fax: 91 124 435 4001

JAPAN

Graco K.K.
1-27-12 Hayabuchi
Tsuzuki-ku
Yokohama City, Japan 2240025
Tel: 81 45 593 7300
Fax: 81 45 593 7301

KOREA

Graco Korea Inc.
Shinhan Bank Building
4th Floor #1599
Gwanyang-Dong, Dongan-Ku,
Anyang-si, Korea 431-060
Tel: 82 31 476 9400
Fax: 82 31 476 9801

SALES/ DISTRIBUTION/ SERVICE

Call today for product information or to request a demonstration.

877-84GRACO (1-877-844-7226) or visit us at www.graco.com.

Graco Inc. is registered to I.S. EN ISO 9001

North America
Customer Service
800-328-0211
Fax 877-340-6427