



**TURBO LINER  
PRODUCTS INC.  
1 W. CAMERON  
KELLOGG, ID 83837  
877-678-8726**

**POLYPRIME 172**  
*Aromatic Urethane  
Polyurea Primer*

**DESCRIPTION**

Polyprime 172 is a single component, liquid applied, aromatic urethane polyurea primer. This primer provides excellent intercoat adhesion.

**FEATURES**

- ❖ One Component
- ❖ Fast Curing

**TYPICAL USES**

- ❖ Polyurethane Elastomeric Surfaces only
- ❖ Pedestrian Decking

**COLOR**

Amber

**PACKAGING**

- 1 gallon (3.78 liter) can
- 5 gallon (19 liter) pail
- 55 gallon drum, net fill 50 gallons (189 liters)

**MIXING**

Before application, Polyprime 172 must be mixed thoroughly. Closed-top metal cans can be shaken or rolled to mix material.

**APPLICATION**

Polyprime 172 should be applied at the rate of 1 gallon/300 sq. ft. (0.135 liters/m<sup>2</sup>) It can be applied using an airless sprayer, brush, or phenolic resin core roller.

Allow Polyprime 172 to dry at 70°F (21°C) and 50% relative humidity for one hour before applying the coating.

Recommended surface temperature should be greater than 50°F (10°C) and at least 5°F above the dewpoint.

Polyprime 172 is very sensitive to heat and moisture. Higher temperatures and/or high humidity will significantly accelerate the cure time.

Low temperature and/or low humidity extend the cure time.

**EQUIPMENT CLEANUP**

Equipment should be cleaned with an environmentally safe solvent, as permitted under local regulations, immediately after use.

**STORAGE**

Polyprime 172 has a shelf life of six (6) months from date of manufacture in original, factory sealed containers.

**TECHNICAL DATA**

Coverage Rate .....	1 gal/300 sq. ft. 0.135 l/m <sup>2</sup>
Dry Film Thickness per Coat .....	3.6 ± 0.1 mils 91.4 ± 3 microns
Specific Gravity .....	1.07
Total Solids by Weight, ASTM D-2369 .....	78 ± 2%
Total Solids by Volume, ASTM D-2697 .....	76 ± 2%
Viscosity at 75°F (24°C) .....	300 ± 100 cps
Volatile Organic Compounds, ASTM D-2369-81 (excluding exempt solvent) .....	1.65 lb/gal 197 gm/liter

**LIMITATIONS**

Not UV stable.

Surfaces must be dry, clean and free of foreign matter.

Containers that have been opened must be used as soon as possible.

Polyprime 172 is difficult to clean up after it has cured.

Do not dilute under any circumstance.

**WARNING**

This product contains Isocyanates and Solvent.

This product is considered Dangerous Goods. DOT regulations classify it as: **PAINT, Class 3, UN 1263, PG III, FLAMMABLE LIQUID.**

---

***Please read all information in the general guidelines, product data sheets, guide specifications and material safety data sheets (MSDS) before applying material. Published technical data and instructions are subject to change without notice. Contact your local Turbo Products representative or visit our website for current technical data and instructions.***

**LIMITED WARRANTY**

Turbo Products warrants its products to be free of manufacturing defects and that they will meet Turbo Products current published physical properties. Turbo Products warrants that its products, when properly installed by a state licensed waterproofing contractor according to Turbo Products guide specifications and product data sheets over a sound, properly prepared substrate, will not allow water migration for a period of one (1) year. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. There are no other warranties by Turbo Products of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. Turbo Products shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. Turbo Products shall not be responsible for use of this product in a manner to infringe on any patent held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and/or physical movement of the substrate or structural defects are also excluded from the limited warranty. Turbo Products reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator.

**DISCLAIMER**

All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the users responsibility to satisfy himself, by his own information and test, to determine suitability of the product for his own intended use, application and job situation and user assumes all risk and liability resulting from his use of the product. We do not suggest or guarantee that any hazard listed herein are the only ones which may exist. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements, whether in writing or oral, other than those contained herein shall not be binding upon the manufacturer, unless in writing and signed by a corporate officer of the manufacturer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and Turbo Products makes no claim that these tests or any other tests, accurately represent all environments.